COUNTRY FLOWERS

Designed by Elise Lea for RK www.robertkaufman.com





Finished quilt measures: 70" x 90"

Difficulty Rating: Advanced



Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	AMD-18940-23 LAVENDER	2-1/4 yard		J	AMD-18940-43 LEAF	1/8 yard
	В	AMD-18939-23 LAVENDER	1-5/8 yard		K	AMD-18942-43 LEAF	1/8 yard
	C	AMD-18943-21 LILAC	1-1/8 yard		L	AMD-18943-43 LEAF	1/8 yard
	D	AMD-18944-201 JEWEL	1-5/8 yard		М	AMD-18944-9 NAVY	1/4 yard
	E	AMD-18942-10 PINK	1/8 yard		N	AMD-18941-6 PURPLE	1/4 yard
	F	AMD-18939-6 PURPLE	1/8 yard		0	AMD-18944-6 PURPLE	1/4 yard
6	G	AMD-18943-15 IVORY	1/8 yard		Р	AMD-18944-40 EMERALD	1/4 yard
	Н	AMD-18940-14 NATURAL	1/8 yard		Q	AMD-18941-118 RUBY	1/4 yard
100	l	AMD-18939-144 PEACH	1/8 yard		R	AMD-18944-118 RUBY	1/4 yard

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.										
Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/\$KU	Yardage			
	S	AMD-18941-7 GREEN	1/4 yard		Binding	* AMD-18944-201 JEWEL *Also used for Fabric D	2/3 yard			
	Т	AMD-18941-201 JEWEL	1/4 yard							
F	2019, Robert Kaufman use only - Not for resal	е			will also need: yards for backing					

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, cut:

four 7-1/4" x WOF strips. Subcut:

eighteen 7-1/4" squares for the large flying geese

fourteen 3-1/2" x WOF strips. Subcut:

seventy-two 3-1/2" squares

Sew the remaining eight strips together, end-to-end and set aside for the outer borders.

From Fabric B, cut:

two 21" x WOF strips. Subcut:

three 21" squares. Cut in half along both diagonals and set aside for the side setting triangles. You will have two triangles left over.

one 12-1/4" x WOF strip. Subcut:

two 12-1/4" squares. Cut in half along one diagonal and set aside for the corner setting triangles.

From Fabric C, cut:

one 3-1/2" x WOF strip. Subcut:

two 3-1/2" squares for the block centers

Trim the remainder of the strip to 2-3/8" wide, then subcut:

eight 2-3/8" squares for the small flying geese

twenty-three 1-1/2" x WOF strips. Set aside for the four-patch strip sets.

From Fabric D, cut:

seven 1-1/2" x WOF strips. Sew the strips together, end-to-end and set aside for the inner borders.

twenty-three 1-1/2" x WOF strips. Set aside for the four-patch strip sets.

one 3-7/8" x WOF strip. Subcut:

eight 3-7/8" squares for the large flying geese

one 4-1/4" x WOF strip. Subcut:

two 4-1/4" squares for the small flying geese

Trim the remainder of the strip to 2" wide, then subcut:

eight 2" squares

From each of Fabrics E-L, cut:

one 3-1/2" x WOF strip. Subcut:

two 3-1/2" squares for the block centers

Trim the remainder of the strip to 2-3/8" wide, then subcut:

eight 2-3/8" squares for the small flying geese

From each of Fabrics M-T, cut:

one 3-7/8" x WOF strip. Subcut:

eight 3-7/8" squares for the large flying geese

one 4-1/4" x WOF strip. Subcut:

two 4-1/4" squares for the small flying geese

Trim the remainder of the strip to 2" wide, then subcut:

eight 2" squares

From the Binding Fabric, cut:


nine 2-1/2" x WOF strips

Assemble the Small Flying Geese

Step 1: Pin two 2-3/8" Fabric E squares in opposing corners of a 4-1/4" Fabric M square, RST. The squares will overlap slightly in the center of the large square. Using a ruler, draw a diagonal line through the squares.



Step 2: Sew scant 1/4" seam on each side of the diagonal line. Set the seam by pressing it flat. Cut along the diagonal line, creating two identical units.



Step 3: Press the fabric toward smaller triangles. Repeat with the second unit.



Step 4: Place one 2-3/8" Fabric E square at the corner of sewn block unit. Draw diagonal line in pencil. Sew a scant 1/4" seam on each side of diagonal line. Set seam (press). Cut along diagonal line, creating two identical units.



Step 5: Press the seam toward smaller triangle. Trim off small dog ears left by the seam allowance. Trim to 2" x 3-1/2" if necessary. Repeat to make four flying geese blocks.



Step 6: Repeat with all remaining 2-3/8" Fabric C and E-L squares and 4-1/4" Fabric D, and M-T squares to make a total of:



eight E/M small flying geese



eight F/N small flying geese



eight G/O small flying geese



eight H/P small flying geese



eight I/Q small flying geese



eight J/R small flying geese



eight C/D small flying geese



eight K/S small flying geese




eight L/T small flying geese

Assemble the Large Flying Geese

Step 7: Pin two 3-7/8" Fabric M squares in opposing corners of a 7-1/4" Fabric A square, RST. The squares will overlap slightly in the center of the large square. Using a ruler, draw a diagonal line through the squares.





Step 8: Sew scant 1/4" seam on each side of the diagonal line. Set the seam by pressing it flat. Cut along the diagonal line, creating two identical units.

Step 9: Press the fabric toward smaller triangles. Repeat with the second unit.





Step 10: Place one 3-7/8" Fabric M square at the corner of sewn block unit. Draw diagonal line in pencil. Sew a scant 1/4" seam on each side of diagonal line. Set seam (press). Cut along diagonal line, creating two identical units.

Step 11: Press the seam toward smaller triangle. Trim off small dog ears left by the seam allowance. Trim to 3-1/2" x 6-1/2" if necessary. Repeat to make four flying geese blocks.



Step 12: Repeat with all remaining 3-7/8" Fabric D and M-T squares and 7-1/4" Fabric A squares to make a total of:



eight D/A large flying geese



eight M/A large flying geese



eight N/A large flying geese



eight O/A large flying geese



eight P/A large flying geese



eight Q/A large flying geese



eight R/A large flying geese



eight S/A arge flying geese



eight T/A large flying geese

Assemble the Blocks



Step 13: Gather: one 3-1/2" Fabric E square four E/M small flying geese four 2" Fabric M squares

Arrange the units into three rows of three. Note the fabric placement and block orientation in the Block Assembly Diagram.

Step 14: Sew the units together to form the rows. Press the seams away from the flying geese units.

Step 15: Sew the rows together, nesting the seams and pressing the seams to one side to form the block center.



Step 16: Gather: the complete block center from Step 15 four 3-1/2" Fabric A squares four M/A large flying geese

Arrange the units into three rows of three. Note the fabric placement and block orientation in the Block Assembly Diagram.

Step 17: Sew the units together to form the rows. Press the seams away from the flying geese units.

Step 18: Sew the rows together, nesting the seams and pressing the seams to one side to form the block center.

The resulting block will measure 12-1/2" square. Repeat Steps 13-18 to make:




two E/M blocks



two F/N blocks




two G/O blocks



two H/P blocks



two I/Q blocks




two J/R blocks



two C/D blocks



two K/S blocks



two L/T blocks

Assemble the Sashing

Step 19: Sew a 1-1/2" Fabric C WOF strip to a 1-1/2" Fabric D WOF strip. Press toward the darker fabric. Repeat to make twenty-three strip sets.



Step 20: Subcut each strip set into twenty-eight 1-1/2" x 2-1/2" units, for a total of six hundred thirty-eight.



Step 21: Pair two units together to make a four-patch, as shown. Sew together and press. Repeat to make three hundred ninteen four-patch units. Set aside thirty-one as the cornerstone units.



Step 22: Sew together six four-patch units, as shown, noting the fabric placement and orientation. Repeat to make twenty-four sashing units like this.



Step 23: Sew together six four-patch units, as shown, noting the fabric placement and orientation. Repeat to make twenty-four sashing units like this.





Step 24: Arrange the Blocks together in diagonal rows, as indicated in the Quilt Assembly Diagram. Sew each row together, using sashing strips between each block and at the beginning and end of each row. Note the fabric placement of the sashing strips. It is important to be careful here so the final quilt matches the cover image. Press seams toward the blocks.

Step 25: Gather the cornerstone four-patch units and remaining sashing strips. Sew each row together, using cornerstones between each sashing strip and at the beginning and end of each row. Press seams toward the cornerstones.

Step 26: Sew the sashing and block rows together in pairs, as shown, pinning and nesting the seams. Press seams open or to the sashing. Sew a side setting triangle to the ends of the rows, and a corner setting triangle to each of the four corners, as indicated in the Quilt Assembly Diagram.

Step 27: Measure the length of the quilt through the center. Cut two Fabric D side border strips to this length. Sew the borders to the sides of the quilt center. Press toward the border. Measure the width of the quilt through the center. Cut two Fabric D top/bottom border strips to this width. Sew the borders to the top and bottom of the quilt center. Press toward the border.

Step 28: Measure the length of the quilt through the center. Cut two Fabric A side border strips to this length. Sew the borders to the sides of the quilt center. Press toward the border. Measure the width of the quilt through the center. Cut two Fabric A top/bottom border strips to this width. Sew the borders to the top and bottom of the quilt center. Press toward the border.

Your quilt top is complete! Baste, quilt, bind and enjoy!

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2019. All rights reserved.