

Film Strip 2

Designed by Robert Kaufman Fabrics

ROBERTKAUFMAN
F A B R I C S

Featuring **Classic Horror Films** Cinema Series

Finished quilt measures 27" x 26-1/2"

Supplies Needed

2/3 yard ARD-14479-283
1/4 yard Kona Black
1/4 yard Kona Corn Yellow
1/8 yard Kona White
1 yard Backing
1 yard Batting

Pattern Level: Enthusiastic Novice

"I am a total beginner and want to learn more!"

For individual use only - Not for resale
Copyright 2014, Robert Kaufman



Notes Before You Begin

- All of the seam allowances are 1/4" unless otherwise noted.
- Remember to measure twice and cut once!
- Please read through all of the instructions before beginning.

Cutting Instructions

ARD-14479-283

- Cut to 19-1/2" x 24"

Kona Black

- Cut 3 strips 1-1/2" x WOF (Width of Fabric).
 - Sew short ends together into one long strip and then subcut into 4 strips 1-1/2" x 27" for vertical sides of film brackets.
- Cut 1 strip 2" x WOF.
 - Subcut into 2 strips 2" x 21-1/2" for the horizontal borders.
- Cut 1 strip 2-1/2" x WOF.
 - Subcut into 24 rectangles 1-1/2" x 2-1/2" for the film brackets.

Kona White

- Cut 2 strips 1-3/4" x WOF.
 - Subcut into 24 rectangles 1-3/4" x 2-1/2".

Kona Corn Yellow

- Cut 3 strips 2-1/2" x WOF for binding

Piecing Instructions:

Step 1

Sew black 2" x 21-1/2" strips to the top and bottom of the panel.

Press seam allowance towards black strips.

Trim strips to width of panel.



Step 2

Sew 2 black 1-1/2" x 27" strips to the right and left sides of the panel.

Press seam allowance towards black strips.

Trim strips to length of panel.

Step 3

Sew white 1-3/4" x 2-1/2" rectangles to black 1-1/2" x 2-1/2" rectangles, alternating white/black (12 black pieces, 12 white pieces).

Press seam allowance towards black rectangles.

Make 2 (one for each side).



Step 4

Sew B&W strips to either side of your quilt top.

Press seam allowance towards center of quilt top.

Trim top and bottom of strips to true up.



Step 5

Sew remaining 2 black 1-1/2" x 27" strips to the right and left sides of the panel.

Press seam allowance towards black strips.

Trim strips to length of panel.

Step 6

Square up quilt top, layer, baste and quilt as desired.

Sew yellow 2 1/2" strips together along short sides to create binding. Sew binding on and enjoy your quilt!