

Mod Geek Tablet Case

Designed by Liz Hansen

ROBERTKAUFMAN
F A B R I C S

www.sewmodernonline.com

Featuring **Mod Geek** by Sarah Johnston

Supplies Needed

3/8 yard: AON-14564-278 (main fabric)
3/8 yard: AON-14566-278 (lining)
1/3 yard: AON-14563-278 (pocket)
1/4 yard: Interfacing (Soft and Stable,
Fusible Fleece, or Batting)
1 sew-in magnetic snap

Pattern Level: Enthusiastic Novice

"I am a total beginner and want to learn more!"

For individual use only - Not for resale

Copyright 2014, Robert Kaufman



Finished project measures 5 1/4" x 7 3/4"

Notes Before You Begin

- All seams are 3/8" unless otherwise noted.
- Please read through the instructions before beginning.
- Remember the golden rule of sewing: "Measure twice, cut once!"

Cutting Instructions

- **AON-14564-278 (main)**
Cut rectangle 8 1/2" x 9" for main fabric front.
Cut rectangle 6" x 12 1/2" for the main fabric back.
- **AON-14566-278 (lining)**
Cut rectangle 6" x 8 1/2" for the lining front.
Cut rectangle 6" x 12 1/2" for the lining back
- **AON-14563-278 (pocket)**
Cut rectangle 6" x 12" for the pocket.
- **Interfacing**
Cut rectangle 6" x 8 1/2" for the front.
Cut rectangle 6" x 12 1/2" for the back.

Piecing Instructions



Step 1: Sew the Box Pleat

- Fold main fabric front in half with WST (wrong sides together) so you have a 4 1/2" x 8 1/2" rectangle.
- Mark the top and bottom edge 3/4" in from folded edge.
- Stitch 1 1/2" in from folded edge.

- Open main fabric front and press pleat flat.
- Match the original fold line to the stitch line. The marks you made 3/4" in from folded edge will become the new fold lines.

Optional: Top stitch 1/4" from edge of each fold

If you are using a fusible interfacing, fuse it to the wrong side of main fabric front and back (follow the manufacturers instructions to fuse).



Step 2: Prep Pocket

- Fold pocket piece in half WST so you have a square 6" x 6".
Optional: Top stitch 1/4" from edge of the fold.

Step 3: Assemble the Outer Body

- Aligning raw edges at bottom and sides, layer pieces:
 - back interfacing
 - back main (right side up)
 - pocket (right side up)
 - front main
 - front interfacing
- Secure with clips or pins.
- Stitch sides and bottom, starting 3/8" from top edge of front, and ending 3/8" from bottom edge.





- If you are using a non-fusible interfacing, trim away interfacing from seam allowance to remove bulk. Clip corners.
- Flip right side out by pulling between front main and pocket.
- Poke out corners.

Step 4: Assemble Lining

- Align the bottom edge and sides of lining front and back RST (right sides together). Stitch sides and bottom, starting 3/8" from top edge of front, and ending 3/8" from edge. Leave the center 4" of the bottom unsewn.



Step 5: Assemble Case

- Insert outer body into lining RST. (outer body should be right side out, lining wrong side out).

- Align the top flap edges, and the top pouch edges. Pin or secure with clips.
- Stitch both edges in one continuous seam, pivoting at previous stitch line and corners. Be careful not to stitch past the previous stitches as this will cause puckering.
- If using a non-fusible interfacing, trim away interfacing from seam allowance to remove bulk. Clip corners.





Step 6: Finishing

- Turn right side out. Poke out corners and press.
- Top stitch the flap and pouch opening.
- Turn under the edges of the 4" opening in bottom lining and press. Edge stitch or hand stitch opening closed.

- Hand stitch the magnetic snap to the lining side of flap and over the box pleat on the center front.



You are finished. Enjoy!