

AMERICAN LEGEND

Designed by Ariga Mahmoudlou for RK Featuring
www.robertkaufman.com

OLD GUYS RULE®



Finished quilt measures: 70" x 90"

Difficulty Rating: **Beginner**

ROBERTKAUFMAN
F A B R I C S

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	AOD-18317-12 GREY	2/3 yard (one full panel)		H	AOD-18319-12 GREY	3/8 yard
	B	AOD-18318-9 NAVY	1/4 yard		I	AOD-18319-4 BLUE	5/8 yard
	C	AOD-18322-15 IVORY	1/4 yard		J	AOD-18319-3 RED	5/8 yard
	D	AOD-18321-3 RED	1/4 yard		K	AOD-18319-205 MULTI	1/2 yard
	E	AOD-18318-184 CHARCOAL	1/4 yard		L	K001-1243 NAVY	1-3/4 yard
	F	AOD-18321-14 NATURAL	1/4 yard		M	ETJ-9864-9 NAVY	2-1/4 yard
	G	AOD-18322-12 GREY	1/4 yard		Binding*	ETJ-9864-9 NAVY <i>*Also used for Fabric M</i>	3/4 yard
<p>Copyright 2018, Robert Kaufman For individual use only - Not for resale</p>				<p>You will also need: 5-1/2 yards for backing</p>			

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, fussy cut:

twenty-four 6" squares

From each of Fabric B, C, E and F cut:

one 6" x WOF strip. Subcut:
four 6" squares

From Fabric D, cut:

one 6" x WOF strip. Subcut:
five 6" squares

From Fabric G, cut:

one 6" x WOF strip. Subcut:
three 6" squares

From Fabric H, cut:

2" wide fussy cut WOF strips, centering the cars on the strip. You will cut every other row of the print. Subcut:
eight 2" x 6" rectangles
eight 2" x 9" rectangles

From each of Fabrics I and J, cut:

2" wide fussy cut WOF strips, centering the cars on the strip. You will cut every other row of the print. Subcut:
fourteen 2" x 6" rectangles
fourteen 2" x 9" rectangles

From Fabric K, cut:

2" wide fussy cut WOF strips, centering the cars on the strip. You will cut every other row of the print. Subcut:
twelve 2" x 6" rectangles
twelve 2" x 9" rectangles

From Fabric L, cut:

eight 4-1/2" x WOF strips. Sew together, end-to-end, then cut:
two 4-1/2" x 62" top/bottom outer borders
two 4-1/2" x 90" side outer borders
ten 2" x WOF strips. Subcut:
twenty-four 2" x 6" rectangles
twenty-four 2" x 9" rectangles

From Fabric M, cut:

seventeen 2" x WOF strips. Sew together, end-to-end, then cut::
nine 2" x 59" top/bottom inner borders/row sashing strips
two 2" x 82" side inner borders
twenty 2" x WOF strips. Subcut:
sixty-four 2" x 9" rectangles
twenty-four 2" x 6" rectangles


From the Binding Fabric, cut:

nine 2-1/2" x WOF strips

Assemble the A Blocks

Step 1: Sew a 2" x 6" Fabric M strip to the left and right edges of a Fabric C square. Press toward the strips. Sew a 2" x 9" Fabric M strip to the top and bottom edges of the square. Press toward the strips.


Step 2: Repeat Step 1 to make:
three from Fabric C
two from Fabric D
two from Fabric E
two from Fabric F
three from Fabric G



Assemble the B Blocks

Step 3: Sew a 2" x 6" Fabric L strip to the left and right edges of a Fabric C square. Press toward the strips. Sew a 2" x 9" Fabric L strip to the top and bottom edges of the square. Press toward the strips.

Step 4: Repeat Step 3 to make:
four from Fabric B
three from Fabric D
two from Fabric E
two from Fabric F



Assemble the C Blocks

Step 5: Sew a 2" x 6" Fabric H strip to the left and right edges of a Fabric A square. Press toward the strips. Sew a 2" x 9" Fabric H strip to the top and bottom edges of the square. Press toward the strips.

Step 6: Repeat Step 5 with all Fabric A squares to make:
four from Fabric H block borders
seven from Fabric I block borders
seven from Fabric J block borders
six from Fabric K block borders



Assemble the Quilt



Step 7: Arrange the A, B and C Blocks into eight rows of six blocks. Note the fabric placement and block orientation in the Quilt Assembly Diagram. Sew each row together, using 2" x 9" Fabric M sashing strips between each block. Press seams toward the sashing.

Step 8: Sew each row together, using 2" x 59" Fabric M sashing strips between each row. Press seams toward the sashing.

Step 9: Sew the top and bottom inner borders to the quilt center. Press toward the borders. Sew the side inner borders to the sides of the quilt center. Press toward the borders.

Step 10: Sew the top and bottom outer borders to the quilt center. Press toward the borders. Sew the side outer borders to the sides of the quilt center. Press toward the borders.

Your quilt top is complete. Baste, quilt, bind and enjoy!

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2018. All rights reserved.