CHINA PLATES

Designed by Darlene Zimmerman www.feedsacklady.com Featuring

Darlene Zimmerman COUNTRY MANOR



Finished quilt measures: 68" x 82"

Pattern Level: Experienced Intermediate



"I know the ropes and would like to test my skills!"

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
		TEN-502-42 COUNTRY MANOR *containing fabrics A - P	one ten square		Н	ADZ-16271-15 IVORY	
		CR-136-20 COUNTRY MANOR *containing fabrics A - P	one charm roll		I	ADZ-16268-4 BLUE	
	A	ADZ-16265-63 SKY			J	ADZ-16266-63 SKY	
	В	ADZ-16268-15 IVORY			К	ADZ-16271-4 BLUE	
	С	ADZ-16270-4 BLUE			L	ADZ-16267-9 NAVY	
	D	adz-16269-63 Sky			м	ADZ-16272-63 SKY	
	E	ADZ-16272-9 NAVY			Ν	ADZ-16269-84 CREAM	
	F	ADZ-16269-4 BLUE			0	ADZ-16270-63 SKY	
	G	ADZ-16268-63 SKY		N SEE	Ρ	ADZ-16266-9 NAVY	

Fabric and Supplies Needed

Yardage Color Fabric Name/SKU Color Name/SKU Fabric Yardage Q ADZ-16269-63 1-1/3 yards S ADZ-16270-63 1-1/2 yards SKY SKY (background) R ADZ-16270-4 5/8 yard Т ADZ-16265-9 2 yards NAVY BLUE You will also need: 2-1/8 yards of 108" wide backing Copyright 2016, Robert Kaufman Tri-Recs (EZ Quilting #8823753A) For individual use only - Not for resale Easy Angle (EZ Quilting #8823759A) Easy Scallop (EZ Scallop #8823754A) optional

Fabric amounts based on yardage that is 42" wide.

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From the Ten Square pack:

Choose a variety of twenty 10" squares for the center of the "plates." Trim each to 8-1/2" square.

From the Charm Roll pack:

Exclude the background print and the two striped prints. From the remaining, choose ten different fabrics for the plate accents. Trim each strip to: 5" x 25" and 5" x 17".

Trim the 5" x 25" strip to 4-1/2". Fold in half and cut eight pairs of Recs triangles from each strip. Set aside.

 4-1/2'		5"
	<u> </u>	

Cut the remaining 17" strips lengthwise to make two 2-1/2" x 17" strips. Cut the strips into eight 2-1/2" squares and eight Easy Angle triangles.



From the background (Fabric Q) cut:

seven 4-1/2" x WOF strips. Subcut: eighty pairs of Recs triangles. four 2-1/2" x WOF strips. Subcut: eighty Easy Angle triangles.

From the light stripe (sashing) fabric, cut:

four 12-1/2" x WOF strips. Open strip and fussy-cut:

forty-nine 2" x 12-1/2" sashing strips using the diagram below.



For the cornerstones:

Cut a charm strip of the dark print in half **lengthwise** to make two 2" x 42" strips. Cut into thirty 2" squares for corner stones.



Assemble the Blocks

Step 1 Sew all the Recs print triangles together with the Recs background triangles. You will have right and left facing units. Press as indicated. At this point the units should measure 2-1/2" x 4-1/2".



Step 2 Sew matching Recs units from Step 1 together as shown. Press the seam open.





Step 3 Sew all the Easy Angle print triangles together with the background triangles. Press toward the print triangle. At this point the squares should measure 2-1/2".

Step 4 Mark a diagonal line on the wrong side of the print 2-1/2" squares. Place a print square on the corner of a contrasting 8-1/2" square, right sides together. Sew on the line, trim the seam allowance to 1/4" and press toward the corner. Repeat with matching squares on all four corners.





Step 5 Matching the accent print corners and the Step 2 units, sew a Step 2 unit to opposite sides of the Step 4 squares. Press toward the center.

Step 6 Sew matching triangle –squares to the ends of two Step 2 units. Press toward the squares. Sew to the sides of the Step 5 units. Press the seams out. At this point the blocks should measure 12-1/2" square. Make twenty blocks.



Assemble the Sashing

Step 1 Sew the blocks together with sashing strips between and on each end. Press toward the sashing. Make five rows of four blocks.



Step 2 Sew four sashing strips and five corner stones together to make a horizontal sashing row. Press toward the sashing. Make six rows.



Step 3 Sew the block rows and sashing rows together, matching and pinning seam intersections. Press the seams toward the sashing.

Add the Borders

Step 1 Cut four 6" border strips lengthwise. Measure and trim two borders the length of the quilt. Sew the borders to the sides of the quilt. Press toward the borders.

Repeat with the top and bottom borders.

Finish the Quilt

Cut 1-1/4" single bias binding strips from the dark stripe fabric. Join the binding strips with diagonal seams pressed open.

Mark the quilt top with the EZ Scallop large tool set at 7-3/4" and inverted scallops with the smaller tool set at 4-1/4", starting at both ends with the large scallop and adjusting the middle scallop or inverted scallop to fit. Leave the ends square. Mark, do NOT cut on the line!



Before binding, stitch along the marked line with a contrasting thread (to make it easier to see) to hold the layers together and prevent shifting.

Align the bias binding strip up to the marked line and sew a 1/4" seam below. Use your 1/4" foot for ease of sewing. Miter the corners.

Trim away the excess quilt, trimming evenly to 1/4". Turn the binding to the back side of the quilt, tuck under 1/4" and stitch in place, covering the stitching line. Sign and date your heirloom quilt!