CHURN ABOUT

Designed by Robert Kaufman Fabrics Featuring *www.robertkaufman.com*

London Calling



Finished quilt measures: 54-1/2" x 64-1/2"

Pattern Level: Enthusiastic Novice



"I am a total beginner and want to learn more!"

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	E105-1268 Oyster	2-2/3 yards		F	SRK-17695-3 RED	1/4 yard
	В	SRK-17696-4 BLUE	1/3 yard	7755 	G	SRK-17692-9 NAVY	1/4 yard
	С	SRK-17694-143 CORAL	1/3 yard		Н	SRK-17694-213 TEAL	1/4 yard
	D	SRK-17693-9 NAVY	1/3 yard		Binding*	SRK-17696-4 BLUE *Also used for Fabric B	5/8 yard
	E	SRK-17689-32 MINT	1/3 yard				
Copyright 2018, Robert Kaufman For individual use only - Not for resale				You will also need: 3-1/2 yards for backing			

Fabric amounts based on yardage that is 43" wide.

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4 unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 43" wide.
- Right sides together has been abbreviated to RST.
- Half-square triangle has been abbreviated to HST.
- Remember to measure twice and cut once!

From Fabric A, cut:

five 5" x WOF strips. Subcut: forty 5" squares for the HSTs

- eight 4-1/2" x WOF strips. Subcut: twenty 4-1/2" squares for the block centers eighty 2-1/2" x 4-1/2" rectangles for the blocks
- ten 1-1/2" x WOF strips. Subcut: fifteen 1-1/2" x 12-1/2" block sashing strips Sew the remaining five WOF strips together, end-to-end, then trim to yield: four 1-1/2" x 51-1/2" row sashing strips

From each of Fabrics B and C, cut:

one 5" x WOF strip. Subcut: eight 5" squares for the HSTs one 4-1/2" x WOF strip. Subcut: sixteen 2-1/2" x 4-1/2" rectangles for the blocks

From each of Fabrics D and E, cut:

one 5" x WOF strip. Subcut: six 5" squares for the HSTs one 4-1/2" x WOF strip. Subcut: twelve 2-1/2" x 4-1/2" rectangles for the blocks

From each of Fabrics F and H, cut:

one 5" x WOF strip. Subcut: four 5" squares for the HSTs Trim the remainder of the strip to 4-1/2" wide, then cut: eight 2-1/2" x 4-1/2" rectangles for the blocks

From Fabric G, cut:

one 5" x WOF strip. Subcut: four 5" squares for the HSTs From the remainder of the strip, cut: four 2-1/2" x 4-1/2" rectangles for the blocks four 4-1/2" x 2-1/2" rectangles for the blocks Use the cutting diagram as a reference for cutting the directional fabric correctly. This will aid in blocks that are oriented correctly in the finished quilt.

From the Binding Fabric, cut:

seven 2-1/2" x WOF strips.



Assemble the Half-Square Triangles

Step 1: Pair a Fabric A 5" square with a Fabric B 5" square, RST. Mark a diagonal line on the wrong side of one square. Sew 1/4" away from both sides of the marked line. Cut on the marked line, creating two half-square triangles (HSTs). Press toward the darker fabric. Trim to 4-1/2" square. Repeat with all remaining 5" squares, pairing a Fabric A square with a Fabric B-H square.



NOTE: For the Fabric G squares, place the fabric so the print is facing the correct direction (right side up, horses facing the right) before placing a Fabric A square on top. Mark a diagonal from upper left to lower right for two of the pairs, and from upper right to lower left for the remaining two G/A pairs. This ensures that the directional fabric is oriented correctly in the finished quilt.

Assemble the Blocks

Step 2: Gather: four Fabric A/B HSTs four Fabric B 2-1/2" x 4-1/2" rectangles four Fabric A 2-1/2" x 4-1/2" rectangles one Fabric A 4-1/2" square

Sew each Fabric A rectangle to a Fabric B rectangle along the longest edge, creating four 4-1/2" square units. Press toward the darker fabric.



Step 3: Arrange the nine units in three rows of three, following the Block Assembly Diagram. Note the placement and block orientation of the print fabric.



Sew the units together to form rows, pressing the rows toward the units completed in Step 2. Sew the rows together, nesting the seams. Press the row seams open or to one side. The resulting block should measure 12-1/2" square.

Repeat with remaining Fabric B pieces, creating four Fabric B Blocks.

Step 4: Repeat Steps 1-3 to create: four Fabric C blocks three Fabric D blocks three Fabric E blocks two Fabric F blocks two Fabric G blocks (Note: Place the Fabric G rectangles and HSTs carefully to ensure proper orientation of the print.) two Fabric H blocks



Step 5: Arrange the blocks together as indicated in the Quilt Assembly Diagram, noting the fabric placement. Sew each row together, using Fabric A block sashing strips between each block. Press seams toward the sashing. Repeat to make five block rows.

Step 6: Sew the rows together, using Fabric A row sashing strips between each row. Press seams toward the sashing.

Your quilt top is complete. Baste, quilt, bind and enjoy!

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2018. All rights reserved.