HAWAIIAN SEAS

Designed by Robert Kaufman Fabrics Featuring www.robertkaufman.com





Finished quilt measures: 86-1/2" x 104-1/2"

Pattern Level: Experienced Intermediate

"I know the ropes and would like to test my skills!"



Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/\$KU	Yardage
	A	AMD-7000-187 PLATINUM	7 yards		J	AYP-15741-246 WATER	1/2 yard
	В	AYP-15739-78 PEACOCK	1-3/8 yard		K	AYP-15742-6 PURPLE	1/2 yard
	С	AYP-15741-59 OCEAN *includes binding	1 yard		L	AYP-15742-7 GREEN	1/2 yard
	D	AYP-15739-6 PURPLE	1/2 yard		M	AYP-15742-34 SAGE	1/2 yard
	E	AYP-15739-7 GREEN	1/2 yard		N	AYP-15742-56 POND	1/2 yard
	F	AYP-15739-59 OCEAN	1/2 yard		0	AYP-15742-78 PEACOCK	1/2 yard
	G	AYP-15740-59 OCEAN	1/2 yard		Р	AYP-15743-6 PURPLE	1/2 yard
	Н	AYP-15740-78 PEACOCK	1/2 yard		Q	AYP-15743-59 OCEAN	1/2 yard
	ı	AYP-15740-108 FUCHSIA	1/2 yard		R	AYP-15743-78 PEACOCK	1/2 yard

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	S	AYP-15744-6 PURPLE	1/2 yard		U	AYP-15744-108 FUCHSIA	1/2 yard
	T	AYP-15744-59 OCEAN	1/2 yard		V	AYP-15744-169 EARTH	1/2 yard
F	1016, Robert Kaufman use only - Not for resc		You will also need: 8 yards for backing				

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, cut:

ten 16-1/2" x WOF strips. Subcut:

twenty 16-1/2" squares

fifteen 2-1/2" x 16-1/2" sashing strips

seven 2-1/2" x WOF strips. Sew the strips together, end-to-end, the trim to yield:

four 2-1/2" x 70-1/2" row sashing strips

eight 4-1/2" x WOF strips. Sew together, end-to-end, then trim to yield:

two 4-1/2" x 88-1/2" side inner borders

two 4-1/2" x 78-1/2" top/bottom inner borders

From Fabric B, cut:

nine 4-1/2" x WOF strips. Sew together, end-to-end, then trim to yield:

two 4-1/2" x 96-1/2" side outer borders

two 4-1/2" x 86-1/2" top/bottom outer borders

From each of Fabrics C-V, cut:

one 16-1/2" square

From the remainder of Fabric C, cut:

2-1/2" x WOF strips for binding


Note: some strips will not be full WOF strips.


Assemble the Blocks

Step 1: Trace and cut the template out onto sturdy card stock or template plastic. Mark to indicate the right side of the template.


Step 2: Place the Fabric C square square right side up on the work surface. Fold the square three times, as follows:


• Fold the bottom edge toward the top. Press.







Fold the left edge toward the right. Press.





• Fold the lower right corner toward the top left corner. Press. The lower left corner will become the center when the fabric is unfolded.






Step 3: Place the template on the folded Fabric C piece, aligning with the lower left corner and left and right edges of the folded triangle. Trace around the template with a fabric marking pen.

Step 4: Remove the template and, without unfolding the fabric, pin the fabric in several

places inside the design.



Step 5: Carefully cut, using sharp pointed scissors, along the marked line of the design. Remove the excess fabric and carefully unfold the design.

Step 6: Repeat Step 2 with a Fabric A square. Unfold and place right side up on the work surface.

Step 7: Center the Fabric C appliqué piece right side up on the Fabric A square, using the fold lines to align the appliqué perfectly. Pin liberally in place. Stitch the edge of the appliqué down by sewing with a straight stitch or small, short zigzag around the entire design, pivoting as needed at each curve. Press the block flat when complete.



Repeat to appliqué each D-V square to a Fabric A square.



Quilt Assembly Diagram

Step 8: Arrange the blocks into five rows of four, referring to the Quilt Assembly Diagram. Sew the blocks into rows, alternating with sashing strips and pressing the seams toward the sashing strips.

Step 9: Sew the rows together, alternating with row sashing strips and pressing the seams toward the sashing.

Step 10: Sew the 4-1/2" x 88-1/2" inner borders to the sides of the quilt top. Press toward the border. Sew the 4-1/2" x 78-1/2" inner border to the top and bottom of the quilt top. Press toward the border.

Step 11: Sew the 4-1/2" \times 96-1/2" outer borders to the sides of the quilt top. Press toward the border. Sew the 4-1/2" \times 86-1/2" outer border to the top and bottom of the quilt top. Press toward the border.

Your quilt top is now complete! Baste, bind, quilt and enjoy!

Template

