

HAY RIDE

Designed by Robert Kaufman Fabrics
www.robertkaufman.com

Featuring **Shades of the Season**



Finished quilt measures: 56" x 72"

Pattern Level: Confident Beginner


*"I have basic block construction down
and would like to learn a new trick!"*

ROBERTKAUFMAN
F A B R I C S

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	CHS-595-42, containing the following:	one Charm Pack			SRKM-16751-15 IVORY	
		SRKM-16749-196 HARVEST				SRKM-16751-16 BROWN	
		SRKM-16750-7 GREEN				SRK-16927-16 BROWN	
		SRKM-16749-7 GREEN				SRKM-16749-14 NATURAL	
		SRKM-16751-191 AUTUMN				SRK-16927-133 GOLD	
		SRKM-16748-196 HARVEST				SRKM-16750-133 GOLD	
		SRKM-16751-196 HARVEST				SRKM-16747-125 SUNFLOWER	
		SRK-16927-5 YELLOW				SRKM-16749-16 BROWN	
		SRK-16927-15 IVORY				SRKM-16750-179 RUST	

Fabric and Supplies Needed - Continued

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
		SRKM-16750-16 BROWN			E	SRKM-16747-125 SUNFLOWER	3/4 yard
		SRKM-16747-2 BLACK			F	SRKM-16747-2 BLACK	1/2 yard
		SRKM-16748-2 BLACK			G	SRKM-16749-7 GREEN	1/3 yard
	B	SRK-16910-15 IVORY	1 yard		H	SRKM-16750-7 GREEN	1/3 yard
	C	SRKM-16748-2 BLACK	1-1/8 yard		I	SRK-16927-133 GOLD	3/8 yard
	D	SRKM-16748-196 HARVEST	1/3 yard		J	SRKM-16749-196 HARVEST	1/3 yard
Copyright 2017, Robert Kaufman For individual use only - Not for resale				You will also need: 3-3/4 yards for backing 5/8 yard for binding			

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From the charm pack squares:

Make eighteen pairs of matching squares. Cut each pair into eight 2-1/2" squares (four units from each 5" square) for a total of one hundred forty-four 2-1/2" squares.

From Fabric B, cut:

nine 2-1/2" x WOF strips. Subcut:

thirty-six 2-1/2" x 8-1/2" sashing strips

five 2" x WOF strips. Sew together, end-to-end, then trim to yield:

two 2" x 45-1/2" side inner borders

two 2" x 48-1/2" top and bottom inner borders

From Fabric C, cut:

two 2-1/2" x WOF strips. Subcut:

twenty-four 2-1/2" squares

six 3-1/2" x WOF strips. Sew together, end-to-end, then trim to yield:

two 3-1/2" x 66-1/2" side outer borders

two 3-1/2" x 56-1/2" top and bottom outer borders

one 9-3/4" x WOF strip. Subcut:

four 9-3/4" squares. Cut each square in half along both diagonals, forming four triangles each.

From Fabric D, cut:

one 9-3/4" x WOF strip. Subcut:

four 9-3/4" squares. Cut each square in half along both diagonals, forming four triangles each.

From Fabric E, cut:

two 11" x WOF strips. Subcut:

four 11" squares. Cut each square once in half along one diagonal.

Trim the remainder of the second strip to 9-1/2" wide. Subcut:

two 9-1/2" squares. Cut each square once in half along one diagonal.

From Fabric F, cut:

three 4-1/2" x WOF strip. Subcut:

twelve 4-1/2" x 8-1/2" rectangles

From each of Fabrics G and H, cut:

two 4-1/2" x WOF strip. Subcut:

twelve 4-1/2" squares

From Fabric I, cut:

eight 1-1/2" x WOF strip. Sew the strips together, end-to-end, then trim to yield:

four 1-1/2" x 3-1/2" side sashing rectangles

two 1-1/2" x 56-1/2" side sashing strips

four 1-1/2" x 50-1/2" row sashing strips


From Fabric J, cut:

three 3-1/2" x WOF strip. Sew the strips together, end-to-end, then trim to yield:
two 3-1/2" x 48-1/2" strips

From the binding fabric, cut:

seven 2-1/2" x WOF strips

Assemble the Sixteen Patch Blocks



Step 1: Gather two sets of eight matching 2-1/2" squares cut from the charm pack. Arrange to form four rows of four squares, following the Block Assembly Diagram. Sew the squares together to form rows, pressing the seams toward the darker fabric. Sew the rows together to form the block, pressing the row seams open or to one side. Resulting block will measure 8-1/2" square. Repeat to make a total of nine 16-patch blocks.

Assemble the Flying Geese Blocks

Step 2: Place a Fabric H square RST at the left edge of a Fabric F rectangle. Mark a diagonal line on the wrong side of the square, as shown. Sew on the marked line and trim away the excess fabric, leaving a 1/4" seam allowance. Press toward the triangle.



Step 3: Repeat Step 1 at the remaining end of the rectangle with a Fabric G square. The resulting flying geese block should measure 4-1/2" x 8-1/2".



Step 4: Repeat with all remaining Fabric F rectangles to make twelve flying geese units.

Assemble the Hourglass Blocks

Step 5: Arrange two Fabric C and two Fabric D triangles to form an hourglass block, taking care to orient the fabric as shown in the example here.



Step 6: Sew one C triangle to one D triangle to form a pair. Repeat with the remaining triangles. Press both seams to the darker fabric.



Step 7: Sew the triangles together along the longest edge, nesting the seams and pressing the seam open or to one side. Trim to 8-1/2" square. Repeat Steps 5-7 to make a total of four hourglass blocks.



Assemble the Quilt Center




Step 8: Arrange the 16-patch and hourglass blocks together as indicated in the Quilt Assembly Diagram, in diagonal rows. Sew each row together, using sashing strips between each block and at the beginning and end of each row. Do not sew the Fabric E triangles to the rows yet. Press seams toward the sashing.

Step 9: Gather the cornerstone squares and remaining sashing strips. Sew each row together as shown in the Quilt Assembly Diagram, using cornerstones between each sashing strip and at the beginning and end of each row. Press seams toward the sashing.

Step 10: Sew the sashing and block rows together in pairs as shown, pinning and nesting the seams to sew a sashing row to the top of each block row. Press seams open or to the sashing. Sew a setting triangle to the ends of each row, aligning the right angle of the setting triangle with the bottom corner of each block row. Press the seams toward the triangles.



Step 11: Sew the rows together, pinning and nesting the seams. Press seams open or to one side. Sew a corner triangle to each corner to complete the quilt center. Press the seams toward the triangles.



Assemble the Quilt Borders



Step 12: Sew the Fabric B side inner borders to the sides of the quilt center. Press toward the borders. Sew the Fabric B top and bottom inner borders to the quilt center. Press toward the borders.

Step 13: Sew six flying geese blocks together, as shown in the Quilt Assembly Diagram, noting the fabric placement and block orientation in the diagram. Press the seams open. Repeat to make a second row of flying geese. Sew one to the top and one to the bottom of the quilt center, pressing the seams to one side.

Step 14: Sew the Fabric I side sashing strips to the left and right edges of the quilt center. Press the seams toward the sashing.

Step 15: Sew a Fabric I row sashing strip to the top and bottom edges of the quilt center. Press the seams toward the sashing.

Step 16: Sew the 1-1/2" x 3-1/2" Fabric I rectangles to the left and right edges of both Fabric J strips. Press the seams toward the sashing. Sew each completed strip to the top and bottom of the quilt center, pressing the seams to one side.

Step 17: Sew the two remaining Fabric I row sashing strips to the top and bottom edges of the quilt center. Press the seams toward the sashing.

Step 18: Sew the Fabric C side outer borders to the sides of the quilt center. Press toward the borders. Sew the Fabric C top and bottom outer borders to the quilt center. Press toward the borders.

Your quilt top is complete! Baste, quilt, bind and enjoy!