Lazy Daisy Redwork

designed by Darlene Zimmerman for Robert Kaufman Fabrics







Lazy Daisy Redwork quilt pattern by Darlene Zimmerman

featuring fabrics from Lazy Daisy Baskets by Darlene Zimmerman


finished quilt measures 46" square; finished blocks measure 8-1/2"

Fabric Requirements


ADZ-12075-3	panel blocks	4 blocks, 1/3yd
ADZ-12080-1	white tone-on-tone	1/2yd
ADZ-12080-99	lightest red print	1/2yd
ADZ-12080-3	medium red print	1/2yd
ADZ-12078-3	dark red & border	1-1/2yds
	backing	2-3/4yds
	batting	50" square

Optional

Using two strands of DMS embroidery floss #321, embroider four of the basket blocks.



outline/back stitch



french knot

(for more embroidery stitch tutorials try www.sublimestitching.com or www.welovefrenchknots.com)

Tool Requirements

Lazy Daisy stitch

Easy Angle (EZ Quilting #8823759) Companion Angle (EZ Quilting #882670139) Easy Scallop (EZ Quilting #8823754)

Cutting Directions for pieced blocks (Make 9)

Cut	To Yield
(2) 2-1/4" x WOF strips	36 Easy Angle triangles
(5) 2" x WOF strips	72 Companion Angle triangles
(1) 2-1/2" x WOF strip	(9) 2-1/2" square
(3) 2-1/2" x WOF strips	(36) 2-1/2" squares
(5) 2-1/2" x WOF strips	(72) 2-1/2" squares
	 (2) 2-1/4" x WOF strips (5) 2" x WOF strips (1) 2-1/2" x WOF strip (3) 2-1/2" x WOF strips

Assembling the Blocks

Step 1: Sew (18) units like this, using the Copanion Angle triangles and the dark red squares. Press the seams toward the red square.

Step 2: Sew (18) units like this, using the Companion Angle triangles and the dark & medium red print squares. Press all seams outwards, toward the white fabric.




(continued)

Assembling the Blocks (continued)

Step 3: Sew (9) units like this, using the dark, medium, and light red prints. Press all seams toward the center.



Step 4: Join the Step 1, 2, and 3 units to make a block. Sew the Easy Angle (smaller triangles) on the diagonal to the corners of the block. Make (9) blocks. Trim both the embroidered basket blocks and the pieced blocks to exactly 9" square, or trim all the blocks the same size.



Cutting Directions for Setting Traingles & Border

From	Cut	To Yield
ADZ-12080-99	(1) 4-3/4" x WOF strip	(8) 4-3/4" squares
	(2) 2-3/4" x WOF strips	(24) 2-3/4" squares
ADZ-12080-3	(3) 2-1/4" x WOF strips	(48) Companion Angle squares
ADZ-12078-3	(5) 5" x WOF strips	borders
	1-1/4" wide bias strips	250" of bias binding

Assembling the Setting Triangles

Step 1: Sew the medium red triangles to adjacent sides of the small light red print squares. Press toward the red triangles. Make (24) units. (**NOTE: The red triangles are larger than needed. Put the excess fabric at the outer edge. You will trim later.**)



Step 2: Sew (2) Step 1 units together as shown. Press the seam open. Make a total of (4) corner units.



Step 3: With the remaining Step 1 units, sew to adjacent sides of the large light red print squares. Press toward the Step 1 units. Make (8) units.



Assembling the Quilt

Step 1: Referring to the photo, arrange the basket blocks, the pieced blocks, and the setting triangles in diagonal rows. Add the corner pieced triangles from Step 2 above. Sew the blocks together in rows, pressing toward the basket blocks.

Step 2: Sew the rows together, pressing the seams open. Add the corner triangle units last. Trim the edges of the quilt straight, leaving at least 1/4" seam allowance.

(continued)

Assembling the Quilt (continued)

- **Step 3**: Measure the quilt through the middle. Trim two 5" wide dark red print strips to this measurement. Sew to the top & bottom of the quilt. Press toward the borders.
- **Step 4**: Piece the remaining three border strips together with the seams pressed open. Trim two borders the length of the quilt. Sew to the sides of the quilt. Press toward the borders.
- **Step 5**: Mark 6" scallops along all sides of the quilt. Leave the corners square.

Finishing the Quilt

Layer, baste, and quilt as desired. Before binding, baste on the marked scalloped line to hold the layers together. Do NOT trim on the marked line until AFTER the binding is sewn on.

Join the binding ends with diagonal seams pressed open. Sew to the marked edge with a 1/4" seam allowance, pivoting at the bottom of the Vs. Trim excess fabric and batting, turn the binding over the edge and tuck under on the back side. Stitch down by hand with matching thread.