


MIGRATING GEESE

Designed by Ariga Mahmoudlou for RK Featuring
www.robertkaufman.com

Patina Handpaints
double ombre



Finished quilt measures: 55" x 71-1/2"







Difficulty Rating: **Beginner**

ROBERTKAUFMAN
F A B R I C S

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	AMD-7000-65 POWDER	3-1/3 yard		H	AMD-7034-233 BERRY	1/4 yard
	B	AMD-7034-372 BLUEGRASS	1/4 yard		I	AMD-7034-18 GRAPE	1/4 yard
	C	AMD-7034-257 CARIBBEAN	1/4 yard		J	AMD-7034-59 OCEAN	1/4 yard
	D	AMD-7034-50 LIME	1/4 yard		K	AMD-7034-80 EVENING	1/4 yard
	E	AMD-7034-367 PUNCH	1/4 yard		L	AMD-7034-184 CHARCOAL	1/4 yard
	F	AMD-7034-239 SORBET	1/4 yard		M	AMD-7034-167 CHOCOLATE	1/4 yard
	G	AMD-7034-317 SALSA	1/4 yard		Binding*	AMD-7034-59 OCEAN <small>*Also used for Fabric J</small>	5/8 yard
<p>Copyright 2019, Robert Kaufman For individual use only - Not for resale</p>				<p>You will also need: 3-1/2 yards for backing</p>			

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, cut:

two 15-1/2" x WOF strips. Subcut:

eight 3-1/2" x 15-1/2" block sashing strips

eight 5" x 15-1/2" block sashing strips

ten 3-7/8" x WOF strips. Subcut:

ninety-six 3-7/8" squares for the flying geese

six 2-1/2" x WOF strips. Sew together, end-to-end, then trim:

two 2-1/2" x 68" side outer borders

two 2-1/2" x 56" top/bottom outer borders

sixteen 2" x WOF strips. Subcut:

fifteen 2" x 15-1/2" row sashing strips

twenty-four 2" x 12-1/2" strips for the blocks

From each of Fabrics B-M, cut:

one 7-1/4" x WOF strip. Subcut:

two 7-1/4" squares, one from the darkest portion of the strip and one from a lightest portion of the strip.

Additionally, from Fabrics B-M, cut:


a total of twenty 2" squares for the cornerstones

From the Binding Fabric, cut:



seven 2-1/2" x WOF strips

Assemble the Flying Geese

Step 1: Pin two 3-7/8" Fabric A squares in opposing corners of a Fabric B square, RST. The squares will overlap slightly in the center of the large square. Using a ruler, draw a diagonal line through the squares.





Step 2: Sew scant 1/4" seam on each side of the diagonal line. Set the seam by pressing it flat. Cut along the diagonal line, creating two identical units.



Step 3: Press the fabric toward smaller triangles. Repeat with the second unit.


Step 4: Place one 3-7/8" Fabric A square at the corner of sewn block unit. Draw diagonal line in pencil. Sew a scant 1/4" seam on each side of diagonal line. Set seam (press). Cut along diagonal line, creating two identical units.



Step 5: Press the seam toward smaller triangle. Trim off small dog ears left by the seam allowance. Trim to 3-1/2" x 6-1/2" if necessary. Repeat to make four flying geese blocks.

Step 6: Repeat with all remaining 3-7/8" Fabric A squares and 7-1/4" Fabric B-M squares to make a total of ninety-six flying geese blocks. *Tip: Keep the flying geese made from each square in separate sets of four.*

Assemble the Blocks



Step 7: Gather:

- four flying geese blocks from the darker Fabric B square
- four flying geese from the lighter Fabric B square
- two 2" x 12-1/2" Fabric A strips

Arrange the flying geese into two columns of four. Note the fabric placement and block orientation in the Block Assembly Diagram.

Step 8: Sew the flying geese together to form the columns. Press the seams up in the left column and down in the right column.

Step 9: Sew the columns together, nesting the seams and pressing the seams to one side.

Step 10: Sew the 2" x 12-1/2" Fabric A strips to the top and bottom edges of the block. Press toward the strips. The block should measure 12-1/2" x 15-1/2".


Repeat Steps 7-10 to make one block each from Fabrics C-M.

Assemble the Quilt

Step 11: Arrange the Blocks together as indicated in the Quilt Assembly Diagram. Sew each row together, using 5" x 15-1/2" Fabric A block sashing strips between each block and 3-1/2" x 15-1/2" Fabric A block sashing strips at the beginning and end of each row. Press seams toward the sashing. Repeat to make four block rows.

Step 12: Gather four cornerstone squares and three 2" x 15-1/2" Fabric A sashing strips. Sew each row together, using cornerstones between each sashing strip and at the beginning and end of each row. Press seams toward the sashing. Repeat to make five sashing rows.

Step 13: Sew the sashing and block rows together, pinning and nesting the seams. Press seams open or to the sashing.



Step 14: Sew the side outer borders to the sides of the quilt center. Press toward the borders. Sew the top and bottom outer borders to the quilt center. Press toward the borders.

Your quilt top is complete. Baste, quilt, bind and enjoy!