# **OMG PILLOWS**

Designed by Robert Kaufman Fabrics www.robertkaufman.com Featuring OMG...LOL

S



For questions about this pattern, please email Patterns@RobertKaufman.com.

# Fabric and Supplies Needed



### Fabric amounts based on yardage that is 42" wide.

## Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

# **Cutting Instructions**

#### From Fabric A, fussy cut:

For each round pillow:

10-1/2" squares, centering the emoji OR cut out individual round faces with a 1/2" seam allowance

For the rectangle pillow:

11" x 11-3/4" rectangle

#### From Fabrics B-E, cut:

one 10-1/2" square for each of the round pillow backings one 11" x 11-3/4" rectangle for the rectangle pillow backing

## Assemble the Round Pillows

Step 1: Match up the Fabric A and backing pieces right sides together and pin. Note the examples illustrated here, showing the two options for fussy cutting the Fabric A pieces. On the wrong side of the front, carefully stitch along the edge of the yellow face. Tip: It may be helpful to lightly trace this line with a pencil on the wrong side of the fabric before pinning. Backstitch at the beginning and end, and leave a 3" opening for turning.



If sewing from fussy cut circles from Fabric A:

Step 2: Trim both fabrics to a 3/8" seam allowance. Clip along the curves every 1/2" all the way around the pillow, being careful not to cut through the stitches. Turn right side out and stuff with filling, carefully pushing out all the edges of the circle. Stitch the opening closed by hand or by machine.

## Assemble the Rectangle Pillows

**Step 1:** Match up the Fabric A and backing pieces right sides together and pin. Using a 1/2" seam allowance, and backstitching at the beginning and end, stitch around all four sides, pivoting at the corners. Leave a 3" opening on the bottom edge.

Step 2: Clip corners, and turn right side out, using a blunt tool to push out the corners. Stuff with filling, and then stitch the opening closed by hand or by machine.