OCEAN VIEWS

Designed by Ariga Mahmoudlou for RK Featuring Awww.robertkaufman.com

Painted Panels



Finished quilt measures: 65" x 65"

Difficulty Rating: Intermediate



Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	А	AMD-17813-197 TROPICAL	2/3 yard (one full panel)		G	AMD-7000-17 IRIS	1/4 yard
	В	AMD-17812-197 TROPICAL	2/3 yard (one full panel)		Н	AMD-11688-76 REGATTA	1/4 yard
	С	AMD-14929-59 OCEAN	1/4 yard		l	AMD-7000-65 POWDER	1-1/3 yard
	D	AMD-7000-23 LAVENDER	3/8 yard		J	AMD-15497-267 ADVENTURE	1 yard
3	E	AMD-15497-257 CARIBBEAN	1/4 yard		Binding*,	AMD-7000-17 Also used for Fabric G	5/8 yard
	F	AMD-7000-81 TURQUOISE	1/4 yard			will also need: ds for backing	
Copyright 2018, Robert Kaufman For individual use only - Not for resale							

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From each of Fabrics A and B, fussy cut:

two 18-1/2" squares

From Fabric C, cut:

four 2" x WOF strips. Subcut:

four 2" x 18-1/2" strips

four 2" x 21-1/2" strips

Tip: Cut one of each length from each WOF strip in order to maximize yardage.

From Fabric D, cut:

four 2" x WOF strips. Subcut:

four 2" x 18-1/2" strips

four 2" x 21-1/2" strips

Tip: Cut one of each length from each WOF strip in order to maximize yardage. one 3-1/2" square

From each of Fabrics E-H, cut:

one 4-1/2" x WOF strip. Subcut:

eight 4-1/2" squares for the HSTs

From Fabric I, cut:

four 4-1/2" x WOF strip. Subcut:

thirty-two 4-1/2" squares for the HSTs

six 4" x WOF strips. Subcut:

sixteen 4" squares

sixteen 4" x 7-1/2" rectangles

From Fabric J, cut:

nine 3-1/2" x WOF strips. Sew together, end-to-end, then trim:

four 3-1/2" x 28-1/2" block sashing strips

two 3-1/2" x 59-1/2" top/bottom outer borders

two 3-1/2" x 65-1/2" side outer borders

From the Binding Fabric, cut:

seven 2-1/2" x WOF strips

Assemble the Half-Square Triangles (HSTs)

Step 1: Pair a 4-1/2" Fabric E square with a 4-1/2" Fabric I square, RST. Mark a diagonal line on the wrong side of one square. Sew 1/4" away from both sides of the marked line. Cut on the marked line, creating two half-square triangles (HSTs). Press toward the darker fabric. Trim to 4" square. Repeat to make sixteen E/I HSTs.



Step 2: Repeat Step 1 to make:



sixteen F/I HSTs.



sixteen G/I HSTs.



sixteen H/I HSTs.

Assemble the Blocks

Step 3: Sew a 2" x 18-1/2" Fabric C strip to the top and bottom of the Fabric A square. Press. Sew a 2" x 21-1/2" Fabric C strip to the left and right edges of a Fabric A square. Press.





Step 4: Gather: four E/I HSTs four F/I HSTs four G/I HSTs four H/I HSTs four Fabric I squares four Fabric I rectangles

Arrange the units as shown, following the fabric placement and orientation in the Block Assembly Diagram. Sew the HSTs, squares and rectangles together to form three rows, as shown.

Sew the rows together to make the block. The block will measure 28-1/2" square.

Repeat Steps 3 and 4 make the second Fabric A Block.



Step 5: Sew a 2" x 18-1/2" Fabric D strip to the top and bottom of the Fabric B square. Press. Sew a 2" x 21-1/2" Fabric D strip to the left and right edges of a Fabric B square. Press.





Step 6: Gather: four E/I HSTs four F/I HSTs four G/I HSTs four H/I HSTs four Fabric I squares four Fabric I rectangles

Arrange the units as shown, following the fabric placement and orientation in the Block Assembly Diagram. Sew the HSTs, squares and rectangles together to form three rows, as shown.

Sew the rows together to make the block. The block will measure 28-1/2" square.

Repeat Steps 5 and 6 make the second Fabric B Block.



Assemble the Quilt



Your quilt top is complete. Baste, quilt, bind and enjoy!

Step 7: Arrange the Blocks together as indicated in the Quilt Assembly Diagram. Sew each row together, using sashing strips between each block. Press seams toward the sashing. Repeat to make two block rows.

Step 8: Gather the 3-1/2" Fabric D square and two sashing strips. Sew the sashing row together. Press seams toward the sashing.

Step 9: Sew the sashing and block rows together, pinning and nesting the seams. Press seams open or to the sashing.

Step 10: Sew the top and bottom outer borders to the quilt center. Press toward the borders. Sew the side outer borders to the sides of the quilt center. Press toward the borders.

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2018. All rights reserved.