ON THE ROAD

Designed by Elise Lea for RK www.robertkaufman.com

Featuring LET'S GO



Finished quilt measures: 56" x 68"

Difficulty Rating: Beginner



Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
(E)	А	SRKD-19006-1 WHITE	2/3 yard (one full panel)		Е	SRKD-19012-184 CHARCOAL	1-3/8 yard
	В	SRKD-19010-3 RED	1/4 yard	A CONTRACTOR OF THE PARTY OF TH	F	SRKD-19008-1 WHITE	1 yard
	C	SRKD-19010-217 GLACIER	1/2 yard		Binding	SRKD-19012-7 GREEN	5/8 yard
	D	SRKD-19011-5 YELLOW	1/8 yard	You will also need: 3-5/8 yards for backing Polyfil (Stuffing) Hand sewing needle & thread			
F	2019, Robert Kaufman I use only - Not for resc		Haria sewing floodic & filload				

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, fussy cut:

one 23" x 32-1/2" center panel

From Fabric B, cut:

four 1-1/2" x WOF strips. Subcut: two 1-1/2" x 32-1/2" side Border 1 pieces two 1-1/2" x 25" top/bottom Border 1 pieces

From Fabric C, cut:

two 4" x WOF strips. Subcut: two 4" x 29-1/2" top/bottom Border 2 pieces two 2-3/4" x WOF strips. Subcut: two 2-3/4" x 34-1/2" side Border 2 pieces

From Fabric D, cut:

two 1" x WOF strips. Subcut: twenty-eight 1" x 2-1/2" rectangles for the road stripes four 1" x 2" rectangles for the road stripes

From Fabric E, cut:

nine 4-1/2" x WOF strips. Sew together, end-to-end, then trim:
two 4-1/2" x 49-1/2" side Border 3 pieces
two 4-1/2" x 29-1/2" top/bottom Border 3 pieces
two 4-1/2" x 58-1/2" side Border 4 pieces
two 4-1/2" x 38-1/2" top/bottom Border 4 pieces
four 1" x WOF strips. Subcut:
twenty-eight 1" x 4-1/2" rectangles for the road stripes

From Fabric F, cut:

six 5-1/2" x WOF strips. Sew together, end-to-end, then trim: two 5-1/2" x 58-1/2" side Border 5 pieces two 5-1/2" x 56-1/2" top/bottom Border 5 pieces

From the Binding Fabric, cut:

seven 2-1/2" x WOF strips

Assemble the Quilt Center

Step 1: Sew the side Border 1 pieces to the sides of the quilt center. Press toward the borders. Sew the top and bottom Border 1 pieces to the quilt center. Press toward the borders.

Step 2: Sew the side Border 2 pieces to the sides of the quilt center. Press toward the borders. Sew the top and bottom Border 2 pieces to the quilt center. Press toward the borders.

Step 3: Sew the top and bottom Border 3 pieces to the quilt center. Press toward the borders. Sew the side Border 3 pieces to the sides of the quilt center. Press toward the borders.



Assemble the Road Stripes

Step 4: Gather:

seven 1" x 2-1/2" Fabric D rectangles eight 1" x 4-1/2" Fabric E rectangles two 1" x 2" Fabric D rectangles

Sew together along the short edges to form a strip, alternating Fabrics D and E and beginning and ending the strip with a 1" x 2" Fabric D piece. Press toward Fabric E. Repeat Step 4 to make a second strip like this.

Step 5: Sew to the left and right edges of the quilt center. Press.

Step 6: Gather:

seven 1" x 2-1/2" Fabric D rectangles six 1" x 4-1/2" Fabric E rectangles

Sew together along the short edges to form a strip, alternating Fabrics D and E and beginning and ending the strip with a Fabric D pieces. Press toward Fabric E. Repeat Step 6 to make a second strip like this.

Step 7: Sew to the top and bottom edges of the quilt center. Press.

Assemble the Outer Borders



Step 8: Sew the top and bottom Border 4 pieces to the quilt center. Press toward the borders. Sew the side Border 4 pieces to the sides of the quilt center. Press toward the borders.

Step 9: Sew the side Border 5 pieces to the sides of the quilt center. Press toward the borders. Sew the top and bottom Border 5 pieces to the quilt center. Press toward the borders. Note the orientation of the print in the Quilt Assembly Diagram.

Your quilt top is complete! Baste, quilt, bind and enjoy!

Assemble the Cars

Step 1: Cut out the cars from Fabric A, following the dotted lines.

Step 2: Place each cut out car right sides together with a scrap of fabric from you choice of Fabrics B-F for the backing of the stuffed car. Cut out a matching shape for each car, being sure to place the Fabric A piece right sides together before cutting each backing piece.



Step 3: Place each car and corresponding backing right sides together. Stitch around the shape, backstitching at the beginning and end of the seam and leaving a 3" opening.



Step 4: Turn the car shape right side out, stuff with stuffing, tuck in the raw edges and hand stitch the opening closed.



This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2019. All rights reserved.