# **PAINTED SEAS**

Designed by Elise Lea for RK www.robertkaufman.com

Featuring ARTISAN

Painted Panels



Finished quilt measures: 64" x 64"

Difficulty Rating: Intermediate



# Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	AMD-17812-197 TROPICAL	2/3 yard (one full panel)		F	AMD-7000-243 CERULEAN	1/8 yard
	В	AMD-17813-197 TROPICAL	2/3 yard (one full panel)		G	AMD-7000-197 TROPICAL	1/4 yard
	С	AMD-7000- 218 AVOCADO	1/4 yard		Н	AMD-7000-228 LAPIS	1/4 yard
	D	AMD-7000-42 PALM	1/4 yard		I	AMD-7000-248 MARINE	2-1/8 yards
	E	AMD-7000-46 PEAR	1/8 yard		Binding*	AMD-7000-197 TROPICAL Also used for Fabric G	5/8 yard
Copyright 2018, Robert Kaufman For individual use only - Not for resale				You will also need: 4 yards for backing			

## Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

### **Cutting Instructions**

#### From each of Fabrics A and B, fussy cut:

two 19-1/2" squares

#### From Fabric C, cut:

two 3" x WOF strips. Subcut: fifteen 3" squares for the HSTs

#### From Fabric D, cut:

two 3" x WOF strips. Subcut: twenty 3" squares for the HSTs

#### From Fabric E, cut:

one 3" x WOF strip. Subcut: thirteen 3" squares for the HSTs

#### From Fabric F, cut:

one 3" x WOF strip. Subcut: thirteen 3" squares for the HSTs

#### From Fabric G, cut:

two 3" x WOF strips. Subcut: twenty 3" squares for the HSTs

#### From Fabric H, cut:

two 3" x WOF strips. Subcut: fifteen 3" squares for the HSTs

#### From Fabric I, cut:

seven 4-1/2" x WOF strips. Sew together, end-to-end, then trim:

four 4-1/2" x 26-1/2" block sashing strips

two 4-1/2" x 56-1/2" top/bottom outer borders

two 4-1/2" x 64-1/2" side outer borders

seven 3" x WOF strips. Subcut:

ninety-two 3" squares for the HSTs

eight 2" x WOF strips. Subcut:

eight 2" x 19-1/2" side block borders

eight 2" x 22-1/2" top/bottom block borders

Tip: Cut one of each length from each WOF strip in order to maximize the yardage one 2-1/2" x WOF strip. Subcut:

eight 2-1/2" squares

#### From the Binding Fabric, cut:

seven 2-1/2" x WOF strips

## Assemble the Half-Square Triangles (HSTs)

**Step 1:** Pair a 3" Fabric C square with a 3" Fabric I square, RST. Mark a diagonal line on the wrong side of one square. Sew 1/4" away from both sides of the marked line. Cut on the marked line, creating two half-square triangles (HSTs). Press toward the darker fabric. Trim to 2-1/2" square. Repeat to make twenty-eight C/I HSTs.



**Step 2:** Repeat Step 1 to make:







forty G/I HSTs.



two C/E HSTs.



two F/H HSTs.

## Assemble the Blocks

**Step 3:** Sew a 2" x 19-1/2" Fabric I strip to the left and right edges of a Fabric A square. Press. Sew a 2" x 22-1/2" Fabric I strip to the top and bottom of the Fabric A square. Press.



**Step 4:** Gather: three C/I HSTs five D/I HSTs three E/I HSTs

Sew together in the following order to make the top block border, noting the orientation in the diagram: C-C-D-C-D-D-E-D-E-E. Press. Sew to the top edge of one Fabric A square.

Repeat to make the bottom block border, and sew to the bottom edge of the block. Press.

Step 5: Gather: four C/I HSTs five D/I HSTs three E/I HSTs one 2-1/2" Fabric I square



Sew together in the following order to make the left block border, noting the orientation in the diagram: C-C-C-D-C-D-D-E-D-E-E-I. Press. Sew to the left edge of the block.

Repeat to make the right block border, and sew to the right edge of the block. Press.

Step 6: Repeat Steps 4 and 5 to make the second Fabric A Block.

**Step 7:** Gather: three F/I HSTs five G/I HSTs three H/I HSTs

Sew together in the following order to make the top block border, noting the orientation in the diagram: F-F-G-F-G-G-H-G-H-H. Press. Sew to the top edge of one Fabric B square.

Repeat to make the bottom block border, and sew to the bottom edge of the block. Press.



**Step 8:** Gather: three F/I HSTs

five G/I HSTs four H/I HSTs

one 2-1/2" Fabric I square

Sew together in the following order to make the left block border, noting the orientation in the diagram: I-F-F-G-F-G-G-H-H-H. Press. Sew to the left edge of the block.


Repeat to make the right block border, and sew to the right edge of the block. Press.

Step 9: Repeat Steps 7 and 8 to make the second Fabric B Block.

#### Assemble the Quilt

**Step 10:** Sew two C/E and two F/H HSTs together to form a four-patch unit, noting the fabric placement and HST orientation in the illustration.





Step 11: Arrange the Blocks together as indicated in the Quilt Assembly Diagram. Sew each row together, using sashing strips between each block. Press seams toward the sashing. Repeat to make two block rows.

**Step 12:** Gather the HST four-patch and two sashing strips. Sew the sashing row together. Press seams toward the sashing.

**Step 13:** Sew the sashing and block rows together, pinning and nesting the seams. Press seams open or to the sashing.

**Step 14:** Sew the top and bottom outer borders to the quilt center. Press toward the borders. Sew the side outer borders to the sides of the quilt center. Press toward the borders.

Your quilt top is complete. Baste, quilt, bind and enjoy!

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2018. All rights reserved.