



Patchwork Jacket

Lightweight & Reversible


Designed By Maxine Charleston




AMD-7004-120




AMD-7004-69




AMD-7002-108




AMD-7201-69




AMD-7202-101



AMD-7202-24



*Scarlet



*Sapphire



AMD-7212-91

Nu-Suede microfiber used for trim.

ROBERTKAUFMAN
F A B R I C S

www.robertkaufman.com

PATCHWORK JACKET

Materials list:

Approx. 100 – 6” squares of four or more different fabric
4 yards of lining material (this is the inside of the jacket and makes it reversible)
4 yard of Tru-grid interfacing to make the pattern
4 yards of muslin or flannel (washed and pressed) for the interlining
4 strips of 2 ½” x 45” material for the binding
75- 1 ¼ squares of ultra-suede of coordinating colors.

Pattern: Lay the Tru-grid interfacing and mark according to the diagram. This material has 1” grid and makes it easy to measure. This is a large size and fits all. For smaller sizes change measurements accordingly. The sleeves have a 2” turn back for a cuff., therefore the lining should compliment the coat squares.



1. The back is cut the same as the front then cut up the center of the front. Allow 6 ½” in the center for the neckline. Round the neckline approx. 12” from the top down the front. Round the back approx. 2” from the top for the neckline.
2. At the top of the pattern begin at the neckline and measure 10-12” along the top from the neckline and draw a line dropping down 2” for the sleeve.
3. Measure 8 ½” for the sleeve and measure the bottom and mark Follow the grid pattern and round under the sleeve.
4. Round the bottom corners if desired.
5. If there are any questions as to the pattern check the drawing.
6. Cut out the pattern and pin. Try it on and adjust to fit.

This is the pattern to cut the muslin or flannel inter lining.

Jacket: With the 6” fashion fabric begin laying the square on the pattern begin in center of the coat for both front and back to form the desired pattern. Move the squares until the pattern is complete. Repeat for the other side. Sew the squares together and press seams open. Sew enough squares together to cover the pattern. Lay the new material made with the blocks on the muslin and pin in place. Place the 1 ¼” squares of ultra suede on the section where the seams meet with the corners on all four seam lines and topstitch in place with matching thread.

- ❖ Sew the pocket in place on both front and back of the jacket. Press seam toward the front. Place the pocket so that it does not get caught in the bottom seam.
- ❖ Sew the fronts to the back under the sleeve seam including the pockets.

Lining or the reversible jacket:



The lining is cut the same as the pattern for the front. Add patch pockets if desired (pattern is not included.) Sew together front and back and under seams. Place inside the coat and baste the outside seams together. Add binding all around the sleeve edges and around the jacket. Enjoy!!

